



STROS - Sedlčanské
strojírny, a.s.
Phone: +420 770 198 816,
+420 777 768 146
E-mail: info@stros.com
www.stros.com

Industrial Elevators **HS SERIES-TWIN**



HS industrial elevators are designed for reliable operation and long life cycles in the harsh environments of various industrial settings, such as power plants, cement plants, lime plants, coal handling facilities, steel mills, refineries, mines etc.

HS SERIES-TWIN

LC: on request / H: up to 1150 ft (350 m) /
S: 150 fpm (45 m/min)

Control: fully automatic, using Selective Collective, or semi-automatic, using direct floor selection (Single Automatic).

We can completely design, manufacture and install the elevator specifically per the customer's requirements and needs.

Our elevators are available in various surface finishes, such as painted, hot-dip galvanized or stainless steel.

Quick and easy installation. Possibility of reaching great heights. No need for an enclosed shaft.

EQUIPMENT OPTIONS:

- Overload protection
- Cable trolley on vertical rails beside the car, or on the mast under the car
- Single-piece or bi-parting car doors
- Erection boom
- Automatic rack lubrication
- Air-conditioned or heated elevator car and control panels
- Elevator Car Counterweight

Technical data	HS SERIES-TWIN
Maximum car internal dimensions (W / L / H)	9'-10 1/2" (3 m) x on request x 7'-10 1/2" (2.4 m)
Maximum load capacity	on request
Standard / non-standard lifting speed	150 fpm (45 m/min) / on request
Standard clear height cage door	6'-8" (2.032 m)
Standard clear width cage door	9'-10 1/2" (3 m)
Motor power	on request
Motor control	Frequency drive
Voltage system	480 V, 3 Phase, 60 Hz
Rated current (480 V)	on request
Main protection (480 V)	on request
Mast	BH / S / H
Maximum lifting height	1150 ft (350 m)
Control	Single Automatic / Selective Collective
Standard / non-standard base landing height above ground	4'-1 1/4" (1250 mm) / on request
Counterweight - Weight	on request

